

Synthoil Race Tech GT1 SAE 10W-60

DESCRIPTION

Synthoil Race Tech GT1 SAE 10W-60 is a modern, fully synthetic, high-performance engine oil formulated for use in four-stroke engines under extreme load. The combination of synthetic base oils and modern additive technology satisfies the requirements of the latest engine designs.

PROPERTIES

- optimum lubrication under extreme conditions
- very high lubrication and ageing stability
- extremely low oil consumption and evaporation loss
- outstanding engine cleanliness
- rapid oil delivery at low temperatures
- miscible and compatible with commercially-available engine oils.
- tried and tested with exhaust catalytic converters

Specifications / Approvals:


ACEA A3/B4
API SL/CF

TECHNICAL DATA

Basis	:	Synthetic oil/additives
Viscosity class	:	10W-60
ASTM colour	:	3.5
Density at 15 °C	:	0.855 g/cm ³
Viscosity at 40 °C	:	155 mm ² /s
Viscosity at 100 °C	:	23,8 mm ² /s
Viscosity index	:	185
Flash point	:	240 °C
Pour point	:	-30 °C
Evaporation loss	:	6.9 %

APPLICATION

For petrol and diesel engines with and without turbocharging. Especially suitable for extreme engine requirements and racing.



PRODUKTINFORMATION



INSTRUCTIONS

The operating instructions of the vehicle and engine manufacturers must be followed.

AVAILABLE PACK SIZE

Synthoil Race Tech GT1
SAE 10W-60

1 l	Part no. 1390 D-GB-I-E-P
1 l	Part no. 1943 D-RUS-UA
1 l	Part no. 8908 D-NL-F-GR-ARAB
5 l	Part no. 1391 D-GB-I-E-P
5 l	Part no. 1944 D-RUS-UA
5 l	Part no. 2876 D-DK-FIN-N-S
5 l	Part no. 8909 D-NL-F-GR-ARAB
20 l	Part no. 1392
60 l	Part no. 1393
205 l	Part no. 1394
lose Ware	Part no. 1399

PI 08/06/13

Our information is based on thorough research and may be considered reliable, although not legally binding.

