Product information

PI 12/13/01/2017

Touring High Tech Tropical Motoroil 20W-50



Description

Touring High Tech Tropical SAE 20W-50 is an all season, high-performance motor oil formulated using state-of-the-art technology. Selected base oils and a high additive content ensure optimum lubrication under extreme operating conditions and during long periods between oil changes.

Properties

- quarantees low oil consumption

- can be used in gasoline and diesel engines with and without turbocharger

- prevents black sludge

- very good dispersion properties

- oil film strength

- high shear stability

- low evaporation loss

- excellent cleaning effect

- mixable with all commercially available motor oils

- tested for catalytic converters

- universal application

- excellent wear resistance

- optimum stability to aging

Technical data

-30 °C Pour point

DIN ISO 3016

Evaporation loss (Noack) 6,5 %

CEC-L-40-A-93

230 °C Flash point

DIN ISO 2592

Total base number 8,5 mg KOH/g

DIN ISO 3771

Sulfate ash 1,0 - 1,6 g/100g

DIN 51575

Color number (ASTM) 4.0

DIN ISO 2049

Specifications and approvals:

ACEA A3 • ACEA B4 • ACEA E7 • API SL • API CH-4

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Mack EO-M Plus • MAN M 3275-1 • MB 228.3

Areas of application

Universal motor oil for gasoline and diesel engines (aspirated diesel engines and diesel engines with exhaust gas turbocharging, with and without charge air cooler). Especially suitable where there are long intervals between oil changes and extreme operating conditions.

Technical data

SAE class (engine oils) 20W-50 **SAE J300**

Density at 15 °C 0,890 g/cm³ DIN 51757

Viscosity at 40 °C 165 mm²/s

ASTM D 7042-04

Viscosity at 100 °C 19.5 mm²/s

ASTM D 7042-04

Viscosity at -20°C (MRV) < 60000 mPas

ASTM D4684

Viscosity at -15°C (CCS) <= 9500 mPas

ASTM D5293

Viscosity index 136

DIN ISO 2909

HTHS at 150°C >=3,5 mPas

ASTM D5481

Application

The operating instructions of the vehicle and engine manufacturers must be followed.

Available pack sizes

1 l Canister plastic 2920

BOOKLET

4 l Canister plastic 2921

D-GB-I-E-P

5 l Canister plastic 2132

BOOKLET

205 l Drum sheet metal 2118

D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-13 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Service-hotline: 0800/8323230 Technical hotline: +49 (0)731/1420-871

www.liqui-moly.de