

Product information

Touring High Tech 15W-40

PI 30/12/01/2017



Description

All-season high-performance motor oil with selected base oils in conjunction with new future-oriented additive technology. Prevents from oil sludge. The formulation has a beneficial effect on sealing materials and thus on the leaktightness of engines. Ensures low oil consumption. High lubricating film stability ensures reliable operation.

Properties

- optimum stability to aging
- high wear resistance
- good cold-start behavior
- suitable for gasoline and diesel engines with and without exhaust-gas turbocharging
- prevents black sludge
- low evaporation loss
- high shear stability
- very good dispersion properties
- good cleaning action
- tested for catalytic converters

Specifications and approvals:

ACEA A3 • ACEA B4 • ACEA E2 • Allison C4 • API SL • API CF • API CG-4 • MAN M 3275-1 • Volvo VDS

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Caterpillar TO-2 • Mack E0-L • MB 228.3 • MB 229.1 • MTU Typ 2 • Peugeot Citroen (PSA) B71 2295

Technical data

SAE class (engine oils)	15W-40 SAE J300
Density at 15 °C	0,880 g/cm ³ DIN 51757
Viscosity at 40 °C	101 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,4 mm ² /s ASTM D 7042-04
Viscosity at -25°C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -20°C (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	147 DIN ISO 2909
HTHS at 150°C	>= 3,7 mPas ASTM D5481



Technical data

Pour point	-30 °C DIN ISO 3016
Evaporation loss (Noack)	10,8 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	8,9 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L4,5 DIN ISO 2049

Areas of application

For engines with high mileage. Universal engine oil for gasoline and diesel engines (with and without exhaust-gas turbocharging and with and without inter-cooling). Especially suitable where there are long intervals between oil changes and extreme running conditions.

Application

The operating instructions of the motor vehicle and engine manufacturer must be followed.

Available pack sizes

1 l Canister plastic	1095 D-F-I
1 l Canister plastic	8905 BOOKLET
1 l Canister plastic	20669 ALGERIEN-BOOKLET
4 l Canister plastic	2911 BOOKLET
5 l Canister plastic	1096 D-F-I
5 l Canister plastic	1862 BOOKLET
5 l Canister plastic	20667 ALGERIEN-BOOKLET

Product information

PI 30/12/01/2017



Touring High Tech 15W-40

Available pack sizes

20 l Canister plastic	1298
	D-GB-I-E-P
60 l Drum sheet metal	1296
	D-GB
60 l Deposit container	1200
	D-GB
205 l Drum sheet metal	1240
	D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.